

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Fuel Cell 18g, 25g, 40g (Niederdruck)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Cartridge

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

OK Befestigung GmbH & Co. KG, Liesentorweg 19 A, 47802 Krefeld, Germany  
Phone: +49 (0)2151 953639, Fax: +49 (0)2151 953649  
www.okbefestigung.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0)2151 953639

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### 2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

##### 2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

F+, Extremely flammable, R12  
Dangerous for the environment, R52/53

#### 2.2 Label elements

##### 2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

Page 2 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 03.03.2015 / 0004  
 Replaces revision of / Version: 10.02.2014 / 0003  
 Valid from: 03.03.2015  
 PDF print date: 04.03.2015  
 Fuel Cell 18g, 25g, 40g (Niederdruck)

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.  
 P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Danger of bursting (explosion) when heated

Possible build up of explosive/highly flammable vapour/air mixture.

Liquid projections or spray may cause frostbite.

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

Pentane	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119459286-30-XXXX
Index	601-006-00-1
EINECS, ELINCS, NLP	203-692-4
CAS	CAS 109-66-0
content %	1-5
Classification according to Directive 67/548/EEC	Extremely flammable, F+, R12 Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R66 R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 2, H411 Asp. Tox. 1, H304 STOT SE 3, H336 Flam. Liq. 2, H225

Hydrocarbons, C6, isoalkanes, < 5% n-hexane	
Registration number (REACH)	01-2119484651-34-XXXX
Index	---
EINECS, ELINCS, NLP	931-254-9 (REACH-IT List-No.)
CAS	(64742-49-0)
content %	1-2,5
Classification according to Directive 67/548/EEC	Highly flammable, F, R11 Irritant, Xi, R38 Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane	
Registration number (REACH)	01-2119486291-36-XXXX
Index	---
EINECS, ELINCS, NLP	926-605-8 (REACH-IT List-No.)
CAS	CAS ---
content %	1-2,5

<b>Classification according to Directive 67/548/EEC</b>	Highly flammable, F, R11 Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R66 R67
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Aquatic Chronic 2, H411 Asp. Tox. 1, H304 Flam. Liq. 2, H225 STOT SE 3, H336

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Respiratory arrest - Artificial respiration apparatus necessary.

#### Skin contact

Normally not irritating to skin.

Wash in water.

Cover frostbite aseptically.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

#### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

At high levels of concentration the propellant dispels the oxygen in air needed to breathe.

Respiratory distress

Nausea

Headaches

Effect on the central nervous system

Coordination disorders

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray/foam/CO<sub>2</sub>/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive gas/air mixtures

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Page 4 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 03.03.2015 / 0004  
 Replaces revision of / Version: 10.02.2014 / 0003  
 Valid from: 03.03.2015  
 PDF print date: 04.03.2015  
 Fuel Cell 18g, 25g, 40g (Niederdruck)

Protective respirator with independent air supply.  
 According to size of fire  
 Full protection, if necessary  
 Cool container at risk with water.  
 Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.  
 Ensure sufficient supply of air.  
 Avoid inhalation, and contact with eyes or skin.

### 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Take precautions against electrostatic charges.  
 Only use equipment that is suitable for this product and the intended pressure and temperature.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Do not store with flammable or self-igniting materials.  
 Not to be stored in gangways or stair wells.  
 Observe special regulations for aerosols!  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.  
 Store upright.  
 Store cool

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 500 mg/m<sup>3</sup>

Chemical Name	Pentane	Content %:1-5	
WEL-TWA: 600 ppm (1800 mg/m <sup>3</sup> ) (WEL), 1000 ppm (3000 mg/m <sup>3</sup> ) (EU)	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		
Chemical Name	Hydrocarbons, C6, isoalkanes, < 5% n-hexane	Content %:1-2,5	
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---	

Page 5 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 03.03.2015 / 0004  
 Replaces revision of / Version: 10.02.2014 / 0003  
 Valid from: 03.03.2015  
 PDF print date: 04.03.2015  
 Fuel Cell 18g, 25g, 40g (Niederdruck)

BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)
-----------	---

<b>Chemical Name</b>	Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane	Content %:1-2,5
WEL-TWA:	350 mg/m3 (cyclohexane)	WEL-STEL: ---
BMGV: ---	Other information: ---	

<b>Chemical Name</b>	Propane	Content %:
WEL-TWA:	1000 ppm (ACGIH)	WEL-STEL: ---
BMGV: ---	Other information: ---	

<b>Chemical Name</b>	Butane	Content %:
WEL-TWA:	600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Hydrocarbons, C6, isoalkanes, < 5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1137	mg/m3	

Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Page 6 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 03.03.2015 / 0004  
 Replaces revision of / Version: 10.02.2014 / 0003  
 Valid from: 03.03.2015  
 PDF print date: 04.03.2015  
 Fuel Cell 18g, 25g, 40g (Niederdruck)

Normally not necessary.

Skin protection - Hand protection:

Normally not necessary.

If applicable

Leather gloves

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter AX (EN 14387), code colour brown.

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol, Substance: Liquid
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Yes
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	Not determined
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined

Solvents content:

Not determined

**SECTION 10: Stability and reactivity****10.1 Reactivity**

The product has not been tested.

**10.2 Chemical stability**

Stable with proper storage and handling.

**10.3 Possibility of hazardous reactions**

No dangerous reactions are known.

**10.4 Conditions to avoid**

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

**10.5 Incompatible materials**

See also section 7.

Avoid contact with strong oxidizing agents.

**10.6 Hazardous decomposition products**

See also section 5.2

No decomposition when used as directed.

**SECTION 11: Toxicological information**

Possibly more information on health effects, see Section 2.1 (classification).

**Fuel Cell 18g, 25g, 40g (Niederdruck)**

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

**Pentane**

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>100	mg/l/4h	Rat		
Skin corrosion/irritation:						Mild irritant, Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation:						Mild irritant
Respiratory or skin sensitisation:						Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						Yes
Respiratory tract irritation:						Mild irritant
Symptoms:						drowsiness, vomiting, cramps, drowsiness, mucous membrane irritation

**Hydrocarbons, C6, isoalkanes, < 5% n-hexane**

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	259354	mg/m <sup>3</sup>	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Irritant
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

**Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane**

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Analogous conclusion
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Drying of the skin.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:					OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Yes
Aspiration hazard:						Yes
Respiratory tract irritation:						Not to be expected



Page 9 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 03.03.2015 / 0004  
 Replaces revision of / Version: 10.02.2014 / 0003  
 Valid from: 03.03.2015  
 PDF print date: 04.03.2015  
 Fuel Cell 18g, 25g, 40g (Niederdruck)

Symptoms:						respiratory distress, drying of the skin., drowsiness, annoyance, heart/circulatory disorders, coughing, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	---

Propane						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Butane						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Fuel Cell 18g, 25g, 40g (Niederdruck)							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

Pentane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	9,87	mg/l	Oncorhynchus mykiss		
Toxicity to fish:	LC50	96h	9,87	mg/l	Salmo gairdneri		

Toxicity to fish:	LC50	96h	9,99	mg/l	Lepomis macrochirus		
Toxicity to daphnia:	EC50	48h	9,74	mg/l	Daphnia magna		
Persistence and degradability:		8d	70	%			
Bioaccumulative potential:	Log Pow		3,39				calculated value

Hydrocarbons, C6, isoalkanes, < 5% n-hexane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	48h	>1	mg/l	Oryzias latipes		Analogous conclusion
Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous conclusion
Toxicity to algae:	ErC50	72h	55	mg/l	Pseudokirchneria subcapitata		Analogous conclusion
Toxicity to algae:	NOELR	72h	30	mg/l	Raphidocelis subcapitata		
Persistence and degradability:		28d	98	%			Readily biodegradable (Analogous conclusion)
Bioaccumulative potential:	Log Kow		4				
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Hydrocarbons, C6-C7, isoalkanes, cyclics, < 5% n-hexane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LL50	96h	12	mg/l	Oncorhynchus mykiss		
Toxicity to daphnia:	EL50	48h	3	mg/l	Daphnia magna		
Persistence and degradability:		28d	98	%			

Propane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Butane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

16 05 04 gases in pressure containers (including halons) containing dangerous substances

Recommendation:

Pay attention to local and national official regulations

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations

Do not perforate, cut up or weld uncleaned container.

Page 11 of 14  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 03.03.2015 / 0004  
 Replaces revision of / Version: 10.02.2014 / 0003  
 Valid from: 03.03.2015  
 PDF print date: 04.03.2015  
 Fuel Cell 18g, 25g, 40g (Niederdruck)

Residues may present a risk of explosion.  
 15 01 04 metallic packaging

## SECTION 14: Transport information

### General statements

UN number: 1950

### Transport by road/by rail (ADR/RID)

UN proper shipping name:

UN 1950 AEROSOLS

Transport hazard class(es):

2.1

Packing group:

-

Classification code:

5F

LQ (ADR 2015):

1 L

LQ (ADR 2009):

2

Environmental hazards:

Not applicable

Tunnel restriction code:

D

EmS:

F-D, S-U



### Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Directive 2010/75/EU (VOC):

100 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections:

11

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

11 Highly flammable.

12 Extremely flammable.

38 Irritating to skin.

51 Toxic to aquatic organisms.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Flam. Liq. — Flammable liquid

Skin Irrit. — Skin irritation

### Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
HGWP Halocarbon Global Warming Potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC Intermediate Bulk Container  
IBC (Code) International Bulk Chemical (Code)  
IC Inhibitory concentration  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
LC lethal concentration  
LC50 lethal concentration 50 percent kill  
LCLo lowest published lethal concentration  
LD Lethal Dose of a chemical  
LD50 Lethal Dose, 50% kill  
LDLo Lethal Dose Low  
LOAEL Lowest Observed Adverse Effect Level  
LOEC Lowest Observed Effect Concentration  
LOEL Lowest Observed Effect Level  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute of Occupational Safety and Health (United States of America)  
NOAEC No Observed Adverse Effective Concentration  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (= Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative

Page 14 of 14  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 03.03.2015 / 0004  
Replaces revision of / Version: 10.02.2014 / 0003  
Valid from: 03.03.2015  
PDF print date: 04.03.2015  
Fuel Cell 18g, 25g, 40g (Niederdruck)

---

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.