









PCLX 320 & 400 PLATE COMPACTORS





FEATURES & BENEFITS

- Low Hand-Arm Vibration design for longer safe usage times.
- Tubular frame designed to protect vulnerable components.
- Baseplate designed for optimised speed and manoeuvrability.
- Lightweight yet durable for easy transport
- Removable 12 litre water tank features a quick-release design.
- Fitted with manual handling points.
- High power 13kN vibration force.
- Engineered to be robust and durable for rental and heavy contractor usage.
- Easy to operate and control, the baseplate does not dig in when dragged backwards or turned.



12LTR QUICK-RELEASE WATER TANK



INTEGRATED SPRAYBAR

TECHNICAL SPECIFICATIONS

PCLX 320		Model	PCLX 400	
LC3251		Part No.	LC4051	
LC3251W	(Water Kit)		LC4051W	(Water Kit)
(mm)	320	Width	(mm)	400
(mm)	927	Operating Height	(mm)	927
(mm)	990	Operating Length	(mm)	990
(mm)	570	Storage Height	(mm)	570
(mm)	790	Storage Length	(mm)	790
(mm)	290 x 390	Plate Contact Area (W x L)	(mm)	370 x 390
(mm)	574	Plate Length	(mm)	574
(Hp / Kw)	3.0 / 2.2	Engine Power	(Hp / Kw)	3.0 / 2.2
	3850	Engine RPM		3850
(kg)	62	Weight	(kg)	66.5
(kg/m^2)	398	Static Pressure	(kg/m^2)	336
(kN)	13	Centrifugal Force	(kN)	13
(m/min)	20	Travel Speed	(m/min)	20
(m/sec ²)	2.42	Vibration level	(m/sec²)	2.48
	LC3251 LC3251W (mm) (mm) (mm) (mm) (mm) (mm) (mm) (Hp / Kw) (kg) (kg/m²) (kN) (m/min)	LC3251 LC3251W (Water Kit) (mm) 320 (mm) 927 (mm) 990 (mm) 570 (mm) 790 (mm) 290 x 390 (mm) 574 (Hp / Kw) 3.0 / 2.2 3850 (kg) 62 (kg/m²) 398 (kN) 13 (m/min) 20	LC3251 (Water Kit) (mm) 320 Width (mm) 927 Operating Height (mm) 990 Operating Length (mm) 570 Storage Height (mm) 790 Storage Length (mm) 290 x 390 Plate Contact Area (W x L) (mm) 574 Plate Length (Hp / Kw) 3.0 / 2.2 Engine Power 3850 Engine RPM (kg) 62 Weight (kg/m²) 398 Static Pressure (kN) 13 Centrifugal Force (m/min) 20 Travel Speed	LC3251 Part No. LC4051 LC3251W (Water Kit) (mm) LC4051W (mm) 320 Width (mm) (mm) 927 Operating Height (mm) (mm) 990 Operating Length (mm) (mm) 570 Storage Height (mm) (mm) 790 Storage Length (mm) (mm) 290 x 390 Plate Contact Area (W x L) (mm) (mm) 574 Plate Length (mm) (Hp / Kw) 3.0 / 2.2 Engine Power (Hp / Kw) 3850 Engine RPM (kg) (kg) 62 Weight (kg) (kg/m²) 398 Static Pressure (kg/m²) (kN) 13 Centrifugal Force (kN) (m/min) 20 Travel Speed (m/min)

Options

OPP/01/DIO	PCLX 320 Block Paving Pad	OPP/51S/DIO	PCLX 320 Water Spray Kit
OPP/02/DIO	PCLX 400 Block Paving Pad	OPP/54S/DIO	PCLX 400 Water Spray Kit
OPP/60/DIO	PCLX 320 & 400 Wheel Kit		



ALTRAD BELLE
Sheen, Nr. Buxton, Derbyshire, SK17 0EU, GB
Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 - Email: sales@altrad-belle.com
www.Altrad-Belle.com
www.ALTRAD-Belle247.com

